



info@c-bear.com
32 (0)11 603 208

C-BEAR BB CHART

27-Jan-14

BB shell ID mm
Width mm

BSA Road	BSA MTB	ITA	BB30	PressFit (BB86/BB92)	Pressfit30 (PF30)	Specialized OSBB 62 (carbon)	Cervelo BBRight	BB386 EVO
68	68	70	42 68 (Road) 73(MTB)	41 86.5 (Road) 92(MTB)	46 68(Road) 73(MTB)	46 62(Road)	46 79(Road)	46 86.5(Road)

Crankset :

Campagnolo UT/PT

Spindle dia = 25mm



BSA/CAM-UT/R
BSA/CAM-UT/C
BSA/CAM-PT/R
BSA/CAM-PT/C



ITA/CAM-UT/R
ITA/CAM-UT/C
ITA/CAM-PT/R
ITA/CAM-PT/C



BB30/CAM-UT/R
BB30/CAM-UT/C
BB30/CAM-PT/R
BB30/CAM-PT/C



PF41/CAM-UT/R
PF41/CAM-UT/C
PF41/CAM-PT/R
PF41/CAM-PT/C



PF30/CAM-UT/R
PF30/CAM-UT/C
PF30/CAM-PT/R
PF30/CAM-PT/C



OSBB62/CAM/R
OSBB62/CAM/C



BBR/CAM-UT/R
BBR/CAM-UT/C



EVO386/CAM-UT/R
EVO386/CAM-UT/C

Campagnolo OT

FSA EVO386

THM Clavicula

TUNE Smart Foot

ZIPP Vumaquad



BSA386/R
BSA386/AC



BSA386/AC



BB30-86/R
BB30-86/AC



PF30-86/R
PF30-86/AC



OSBB62-86/R
OSBB62-86/C



BBR386/R
BBR386/C



EVO386/R
EVO386/C

FSA BB30, SRAM BB30

Spindle dia = 30mm



BB30/R
BB30/AC



PF30/R
PF30/C



OSBB62-BB30/R
OSBB62-BB30/C

FSA Mega Exo

Spindle dia = 24mm



BSA-ROAD/FSA/R
BSA-ROAD/FSA/C



BSA-MTB



ITA/R
ITA/C



BB30-24/R
BB30-24/AC



PF41/FSA/R
PF41/FSA/AC



PF30-24/R
PF30-24/AC



OSBB62-24/R
OSBB62-24/C



BBR24/R
BBR24/C



EVO386-24/R
EVO386-24/C

Race Face X-Type

Spindle dia = 24mm



BSA-ROAD/R
BSA-ROAD/C



BSA-MTB



ITA/R
ITA/C



BB30-24/R
BB30-24/AC



PF41/R
PF41/AC



PF30-24/R
PF30-24/AC



OSBB62-24/R
OSBB62-24/C



BBR24/R
BBR24/C



EVO386-24/R
EVO386-24/C

Rotor 3D, Aquilis, Rex3

Spindle dia = 24mm



BSA-ROAD/R
BSA-ROAD/C



BSA-MTB



ITA/R
ITA/C



BB30-24/R
BB30-24/AC



PF41/R
PF41/AC



PF30-24/R
PF30-24/AC



OSBB62-24/R
OSBB62-24/C



BBR24/R
BBR24/C



EVO386-24/R
EVO386-24/C

Rotor :

3D+, 3DF

Rex 1

Rex 2

Spindle dia = 30mm



BSA30/R
BSA30/AC



BSA30/AC



BB30-86/R
BB30-86/AC



PF30-86/R
PF30-86/AC



OSBB62-86/R
OSBB62-86/C



BBR86/R
BBR86/C



EVO386/R
EVO386/C

Shimano HTII

Spindle dia = 24mm



BSA-ROAD/R
BSA-ROAD/C



BSA-MTB



ITA/R
ITA/C



BB30-24/R
BB30-24/AC



PF41/R
PF41/AC



PF30-24/R
PF30-24/AC



OSBB62-24/R
OSBB62-24/C




BBR24/R
BBR24/C



EVO386-24/R
EVO386-24/C

Specialized - Fact

Spindle dia = 30mm



BB30/R
BB30/AC



OSBB73-FACT
(MTB)



OSBB62-FACT/R
OSBB62-FACT/C

SRAM/Truvativ GXP

Spindle dia = 24/22mm



BSA/GXP/R
BSA/GXP/C



BSA/GXP/A



ITA/GXP/R
ITA/GXP/C



BB30-24/GXP/R
BB30-24/GXP/AC



PF41/GXP/R
PF41/GXP/AC



PF30-24/GXP/R
PF30-24/GXP/AC



OSBB62-GXP/R
OSBB62-GXP/C



BBR24/GXP/R
BBR24/GXP/C



EVO386-24/GXP/R
EVO386-24/GXP/C



A = ATB/MTB
AC = MTB/Cyclocross
C = Cyclocross
R = Race